





DomeCam Mini

Wired security IP camera



True
WDR

IP65



Product versions

DomeCam Mini (5 Mp/2.8 mm)

Wired security IP camera with up to 2,880 × 1,620 px resolution and 100°–110° viewing angle

DomeCam Mini (8 Mp/2.8 mm)

Wired security IP camera with up to 3,840 × 2,160 px resolution and 100°–110° viewing angle

DomeCam Mini (5 Mp/4 mm)


Wired security IP camera with up to 2,880 × 1,620 px resolution and 75°–85° viewing angle

DomeCam Mini (8 Mp/4 mm)


Wired security IP camera with up to 3,840 × 2,160 px resolution and 75°–85° viewing angle

How it works

DomeCam Mini operates seamlessly by utilizing Ajax Cloud for transmitting system events, while the proprietary JetSparrow technology ensures fast peer-to-peer transmission of video data. With AI-analysis capabilities, DomeCam Mini can detect and recognize object types, such as humans, vehicles, and pets. This allows the surveillance system to record only relevant events and use less storage. To make surveillance precisely selective, it is possible to enable cameras only when the system is armed.




DomeCam Mini can operate without Ajax NVR, saving the archive on the SD card (if installed)



Uncompromising security and privacy

- Passwordless camera authentication with mTLS handshake
- Video stream with TLS encryption
- Real-time privacy control via the apps
- Account security with passcodes, biometrics, and two-factor authentication
- Session control for added protection
- Owner-only access to media data recorded on the hard drive
- Accelerometer to notify of impacts or dismantling (in future releases)
- Components only from white-listed vendors in NDA




Seamless user experience

- Objects AI recognition: humans, vehicles, pets¹
- High-resolution visual verification for alarms with video scenarios¹
- Easy transition from notifications feed to on-site video recordings¹
- Cameras synchronization with security modes
- Real-time oversight with a customizable video wall
- True WDR for exceptional image quality




Advanced Security Distribution Limited
sales@asdltd.ie +3530473 4550 www.asdltd.ie




Smooth archive navigation

- JetSparrow peer-to-peer streaming
- Instant live view
- Fast archive navigation with filters and calendar
- Dual streaming for instant preview
- Video clip export in a few clicks



Easy installation and maintenance

- Connection via QR code
- Configuration via Ajax apps
- Adjustable motion detection zones available in the apps
- Real-time supervision with health checks



Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Features Resolution 5 MP Model: Up to 2,880 × 1,620 px @ 25 fps (3K UHD) 8 MP Model: Up to 3,840 × 2,160 px @ 20 fps (4K UHD) Lens 2.8 mm: 100°–110° Viewing Angle 4 mm: 75°–85° Viewing Angle Day/Night Switch Automatic Image processing True WDR (hardware and software) Video Compression H.265, H.264 Bitrate 100 Mbps full-duplex Simultaneous Live View Up to 5 Channels User Access Up to 200 Users Alarm Trigger Motion Detection, AI-recognition, Detector alarm, Automation scenarios	Compatibility Hubs All Ajax hubs (up to 200 cameras in one Ajax system) Video recorders NVR	Power supply Power supply unit 12 V ± 20% =, 1 A Up to 7.5 W of mains power consumption Ethernet port PoE Standard 802.3at, Class 3
	Enclosure Dimensions 113 × 60 mm Weight 360 g Colors Black White Operating temperature range from –30 °C to +60 °C from –22 °F to +140 °F Operating humidity up to 90%	Compliance CE FCC RED RoHS NDAA
	Complete set DomeCam Mini Installation template Installation kit Quick start guide	

¹ Requires an SD-card installed or connection to NVR with a hard drive

